

DETEX

ECL 230D - Exit Control

Features:

- · Single point deadbolt locking device, 1" throw
- Unauthorized pressing of exit bar emits high decibel, 100db alarm
- · Inside key control allows alarm bypass
- · Accepts rim cylinder
- UL listed panic hardware
- 9 volt standard battery included
- Required Rim (not included) Cylinder:



V40EB – Exit Control

Features:

- · 100db alarm
- · Powered by 9 volt battery included
- Low battery alert
- · Red flashing LED alert when not armed
- Inside key control allows alarm bypass
- · Accepts 1-1/8" mortise cylinder
- · Latch bolt monitoring standard
- Required cylinder: Mortise (Not Included)

Stocked Product

- V40EB for 36" door
- V40EBL for 48" door

Code Compliance:

- UBC97 standard 7-2
- Exceeds ADA, CA title 19 ANSI / BHMA requirements



EAX-500

- · Low Cost, Self Contained door alarm with piezo horn
- Surface door mount only
- · Patented plastic template allows for fool proof alignment of internal magnetic door contact
- · Temper resistant housing
- Taper cover allows installation on 2" minumum stile doors
- Inside key control requires 1-1/8" mortise cylinder with standard Yale cam (supplied less cylinder)
- · For outside key control (optional) use RIM cylinder (not supplied)

Stocked Product

• EAX500

EAX-500 - Is designed for applications that require an alarmed exit device on secured doors. Replaces old model EA-500

