

3750 Multi Slide System



3750 Multi Slide System

Features and Benefits

□ Sizing

- Standard sizing in 9', 12', and 15' x 8' in 3 panel Configuration.
- Standard sizing in 12', 16', and 20' x 8' in 4 panel Configuration.
- Maximum panel size is 5' x 8' or 40 sq ft.
- Maximum frame width of 3 panel door system at 15'.
- Maximum width of 4 panel door system at 20'.
- Custom sizing available.

□ Frame

- KD or welded main frame.
- 7 $\frac{3}{4}$ " total width 6 $\frac{3}{4}$ " jamb depth all PVC multi-chambered profile frame system (on 3 panel).
- 10 $\frac{3}{16}$ " total width 9 $\frac{3}{16}$ " jamb depth all PVC multi-chambered profile frame system (on 4 panel).
- Integrated nail fin application with 1" or 1 $\frac{3}{8}$ " set back.
- Full length weather stripping on all 4 frame components.
- Integrated sill drainage with snap-in sill covers.

□ Sash

- Fully welded vinyl sash with internal aluminum reinforcement with $\frac{7}{8}$ " standard IG, or a 1 $\frac{1}{4}$ " triple insulated glass system.
- Many high energy-efficient glass options for the most extreme temperature sensitive regions.
- Standard glazing, Cardinal™ LoE 366® dual glazed tempered glass.
- All stiles are metal reinforced for extreme wind load resistance.
- Unique internal drainage system to minimize risk of seal failures.
- Interior glazed for better performance.

□ Hardware

- Truth Nexus 2 point lock with opposing lock points.
- Anti-lock feature preventing a "false" sense of lock up.
- Flush mount handle - does not protrude into the room.
- Deep finger pocket - provides superior grip area for moving large door panels.
- Recessed thumb slide intuitive locking and unlocking of panel.
- Stainless steel roller housing and composite wheels with side adjustment, AAMA rated to carry a 500 pound panel for 10,000 cycles without change to adjustment.
- Hardware colors; white, black powder coat, and brushed chrome.

□ Extruded Vinyl Colors



□ Optional Exterior Coated Stocked Colors



□ Optional

- Black Interior and Exterior Specialty Laminate



Signature

Flush Mount



3 Panel Configuration; oxx



3 Panel Configuration; oxx



3 Panel Configuration; xxo



3 Panel Configuration; xxo



3 Panel Configuration; xxo



3 Panel Configuration; xxo



3 Panel Configuration; oxx



3 Panel Configuration; oxx



3 Panel Configuration; xxo



3 Panel Configuration; xxo



3 Panel Configuration; oxx



3 Panel Configuration; oxx



3 Panel Configurations; oxx and xxo



3 Panel Configurations; oxx and xxo



Corner 6 Panel Configurations; oxx and xxo



Corner 7 Panel Configurations; oxx and xxxo



4 Panel Configurations: oxxx and xxxo



4 Panel Configurations; oxxx and xxxo



3 Panel Configurations; oxx and xxo



3 Panel Configurations; oxx and xxo



Corner 5 Panel Configurations: oxx and xo



Corner 5 Panel Configurations; oxx and xo



4 Panel Configuration; oxxx



4 Panel Configuration; oxxx



4 Panel Configuration; xxxo



4 Panel Configuration; xxxo



3 Panel Configuration xxo with Integrated Retractable Pleated Screen



3 Panel Configuration xxo with Integrated Retractable Pleated Screen

Features and Benefits

Frame

- KD or welded main frame
- 7 $\frac{3}{4}$ " Total width 6 $\frac{3}{4}$ " Jamb depth all PVC multi-chambered profile frame system (on 3 panel)
- 10 $\frac{3}{16}$ " Total width 9 $\frac{3}{16}$ " Jamb depth all PVC multi-chambered profile frame system (on 4 panel)
- Integrated nail fin application with 1" or 1 $\frac{3}{8}$ " set back
- Full length weather stripping on all 4 frame components
- Integrated sill drainage with snap-in sill covers

Sizing

- Standard sizing in 3 panel and 4 panel configuration
- Maximum panel size is 5' x 8'
- Maximum frame width of 3 panel door system at 15'
- 15' Maximum width of 4 panel door system at 20' Custom sizing available


Sash

- Fully welded vinyl sash with internal aluminum reinforcement with 7/8" standard IG, or a 1 $\frac{1}{4}$ " triple insulated glass system. Many high energy-efficient glass options for the most extreme temperature sensitive regions.
- Standard glazing, Cardinal™ LoE 366® Dual Glazed tempered glass
- All stiles are metal reinforced for extreme wind load resistance
- Unique internal drainage system to minimize risk of seal failures

Hardware

- Truth Nexus 2 point lock with opposing lock points
- Anti-lock feature preventing a "false" sense of lock up
- Flush mount handle - does not protrude into the room
- Deep finger pocket - provides superior grip area for moving large door panels
- Recessed thumb slide intuitive locking and unlocking of panel
- Stainless steel roller housing and composite wheel with end adjustment, AAMA rated to carry a 500 pound panel for 10,000 cycles without change to adjustment
- Hardware Colors; White, Black powder coat, and Brushed Chrome

Extruded Vinyl Colors



Optional Stocked Coated Colors



Optional Hardware



Standard Hardware



